

Description: 7/0.2mm Def-Stan Multicore Type A Unscreened, Duct Grade Cable



Construction

Conductor Material : Tinned Copper, 7/0.2mm
 Conductor Insulation : Polyvinyl Chloride (PVC)
 Overall Tape : Polyester
 Inner Sheath Material : Polyvinyl Chloride (PVC)
 Inner Sheath Colour : Black
 Outer Sheath Material : Low Density Polyethylene (LDPE)
 Outer Sheath Colour : Black
 Core Identification :

1	Red	7	Brown
2	Blue	8	Violet
3	Green	9	Orange
4	Yellow	10	Pink
5	White	11	Turquoise
6	Black	12	Grey

Electrical Characteristics

Nominal Conductor Resistance @ 20°C : < 92 Ω/km
 Insulation Resistance : > 200 MΩ.M
 Voltage Rating : 440V rms up to 1600 MHz
 Test Voltage : 2.5kV for 5 Minutes
 Current Rating : 1 amps

Physical Characteristics

Overall Diameter : See Table
 Min. Bend Radius : 7.5 x OD
 Temperature Rating : -0°C to 70°C
 Weight : See Table

Standards

RoHS3 Compliant : Yes
 CE Compliant : LVD (2014/35/EU)
 CPR Classification : Fca (EN50575:2014+A1:2016)
 Generally Manufactured to : Def Stan 61-12 Part 4

Part No.	Size	No. of Cores	Weight kg/km	O/D mm
39200206D-F00	7-2-6A	6	52	7.2
39200208D-F00	7-2-8A	8	56	8.1
39200212D-F00	7-2-12A	12	68	8.9